

HS LVT Flooring

Click 5mm, 0.5

Dated: 4/2013

Product specification according EN 649

Characteristics	Standard	Unit	Result
Type of floor covering	EN 649		Heterogeneous PVC
Surface treatment			Polyurthane
Pattern			Wood and Stone
Behaviour to fire	EN 13501-1	Class	Bfl - s1
Resistance to slip	EN 13893	Class	DS
Plank size	EN 426	mm	149.86 x 911.86 /99.06 x 911.86
Tile size	EN 426	mm	454.66 x 454.66
Total Thickness	EN 428	mm	5
Wear layer thickness	EN 429	mm	0.5
Total weight	EN 430	g/m ²	9700
Residual Indentation	EN 433	mm	≤ 0,1mm
Color fastness	ISO 105 B02		≥ 6
Resistance to chemicals	EN 423		Resistant against common used acids, alkalis, oils and grease depending on concentration and time.
Resistance to wear	EN 649		T
Thermal resistance	EN 12667	m ² K/W	N/A
Dimensional stability and curling after exposure to heat	EN 434	%	≤ 0,12
Castor chair suitability	EN 425		Yes

Classification according EN 685



Class Domestic - Heavy



Class Commercial - Heavy



Class Industrial - General



Polyvinylchloride
floor coverings
according EN 14041: 2008

HS floor coverings have to be installed according valid HS Floor installation manual as well as recognized trade/technical standards. Routine maintenance cleaning is essential for long-term maintenance of value of the floor coverings. Hongsheng reserve the right to change the technical specifications.

HongSheng Investment Limited

11th FL., #12 Zhangjiang Innovation Park No.399,
Keyuan Road, Pudong, Shanghai, China #201203

Tel : 86-21-5080-8266 (ext.826)

Fax : 86-21-5080-9887

Email: hongsheng@hongsheng-global.com